



Safety Data Sheet (SDS)

SDS-800- Acrylonitrile-Butadiene-Styrene (ABS)

Section 1: Identification

Product Name: SATRAN Acrylonitrile-Butadiene-Styrene (ABS)

Product Series: 800, 800R, 805, 800GF10, 800GF20, 800HG, 800HH

Company Name: MRC Polymers Inc.
3307 S. Lawndale Ave
Chicago, IL - 60623

Emergency Contact Phone Number: (815) 221-6400

Section 2: Hazard(s) Identification

Exposure: This product as shipped (pelletized) should not present a health hazard during normal handling and processing as the glass and/or minerals and/or colorants and/or flame retardants and/or other additives are wetted by the polymer. Fabrications and processing operations should be reviewed to avoid generation of dusts and/or fiber particles, which may be considered hazardous.

Eyes: Solid or dust may cause irritation or cornea injury due to mechanical action.

Skin Contact: Prolonged or repeated exposure may cause skin irritation but essentially nonirritating to skin. Mechanical injury only. Skin absorption is unlikely due to physical properties.

Inhalation: Dust or Vapors may cause irritation. Filler/Additives in this product are non-resorbable because they are encapsulated in the product and are not expected to be release under normal processing conditions.

Ingestion: May cause choking if swallowed. Single dose oral toxicity is believed to be very low. Considered being physiologically inert.

Systemic and Other Effects: Repeated exposure to particles generated by grinding fiberglass-reinforced materials may result in implantation of particles in the skin. Other additives are not anticipated to cause any significant adverse effects. Pigments and dyes are fully encapsulated in the resin and are not expected to cause any hazardous condition when processed according to manufacturing procedures. Results of in vitro mutagenicity studies have been inconclusive Styrene monomer is listed as possible carcinogen by IARC. Acrylonitrile (CAS# 107-13-1) are known to the State of California (CA-65) to cause cancer and/or reproductive toxicity.

Fire Hazards: Dense black smoke and intense heat emits when burned without sufficient oxygen. Toxic fumes are released in fire situations.

Unusual Fire and Explosion Hazards: The product can form an explosive dust/air mixture. Avoid dust formation and control ignition sources; employ grounding, venting and explosion relief provisions in accord with accepted engineering practices in operations capable of generating dust and/or static electricity.

Section 3: Composition/information on Ingredients

Ingredients	CAS Number	Typical Levels, %
Acrylonitrile-butadiene-styrene (ABS)	(9003-56-9)	80-90
Glass Filler	(065997-17-3)	10-20
Proprietary Modifiers		< 5
Non-regulated lubricants/stabilizers		< 2

The resin in specifically designated colors may contain commercially available dyes and pigments, generally at levels less than 1 percent, but sometimes at levels greater than 1 percent, including titanium dioxide, carbon black, iron, ultra marine blue, and other insoluble metal salts at less than 5 percent.

This document is prepared pursuant to OSHA Hazard Communication Standard (29 CFR 1910.1200). In addition, other substances not hazardous to this OSHA standard may be listed. Where proprietary ingredient shows, the identity of this substance may be made available as provided in 29 CFR 1910.1200 (I).

Section 4: First-aid Measures

Eyes: Remove contact lenses at once. Flush with plenty of water, lifting upper and lower lids occasionally. Seek medical attention.

Skin: Contact with molten resin can cause severe thermal burns. Cool rapidly with water and immediately seek medical attention. Do not attempt removal of plastic without medical assistance. Do not use solvent for removal.

Ingestion: No adverse effects anticipated by this route of exposure incidental to proper industrial handling. If a large amount is swallowed, seek medical attention.

Inhaled: No adverse effects anticipated by this route of exposure.

Section 5: Fire-fighting Measures

Extinguishing Media: Water fog (best), carbon dioxide, dry chemical.

Flash point: Not applicable.

Auto ignition: Not applicable.

Fire-Fighting Procedures: Wear self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode and full body protection when fighting fires. Water may be used to keep fire-exposed containers cool until fire is out. Water, Carbon dioxide and dry chemicals can be use as fire extinguishing media.

Section 6: Accidental Release Measures

Emergency Action: No special environmental precautions required.

Spill/Leak Procedure: Containment of this material should not be necessary. Sweep up or gather material and place in appropriate container for disposal.

Section 7: Handling and Storage

Practice reasonable care and cleanliness. Ventilation should be provided at processing machinery to control fumes. There should be proper dust collection systems in place to avoid any dust accumulation. Store in a dry place away from moisture, excessive heat and source of ignition.

Section 8: Exposure Controls/Personal Protection

Skin: Wear clean, long-sleeved, body-covering clothing. Under dry conditions, cloth gloves should provide adequate protection from molten plastic. If molten polymer gets in contact with the skin, cool rapidly with water and do not attempt to remove plastic without medical assistance. Seek immediate medical attention.

Respiratory: If handling at elevated temperatures and overexposure has been determined, an air-respirator is advised in the absence of proper environmental control.

Ventilation: Provide sufficient mechanical ventilation to maintain exposure level below the level of over exposure. Seek immediate medical attention of any symptom like coughing, difficulties in breathing or any other problem develops.

Eyes: Wear safety glasses in compliance with OSHA regulations.

Section 9: Physical and Chemical Properties

Boiling point: Not applicable.
Melting point: Soften gradually over wide range of temperature.
Vapor pressure: Negligible.
Specific gravity (H₂O= 1) : >1.
Percent volatile: Negligible.
Appearance: Natural or opaque colors solid pellets.
Odor: Slight.
Water solubility: Insoluble.
pH: Not applicable.

Section 10: Stability and Reactivity

Hazardous Polymerization: Will not occur.

Stability: Polymer decomposes above 300° C (572° F).

Incompatibility: None known.

Hazardous Decomposition Products: May include and not limited to Carbon dioxide/monoxide, phenolic compounds, styrene, hydrocarbons, and acrylates at elevated temperatures.

Section 11: Toxicological Information

Likely Routes of Exposure: Eyes and skin contact.

Acute Effects: Irritation of eyes and skin.

Oral Toxicity LD50 Not Available;

Inhalation Toxicity LD50 Not Available.

Chronic Effects: None known.

Symptoms: Irritation of eyes and skin.

Carcinogenicity: This product has not been found to be carcinogenic by the NTP, ACGIH, IARC or OSHA.

Further information: This product has no known adverse effect on human health

Section 12: Ecological Information

Ecotoxicity: No known or expected ecotoxicity

Persistence and Biodegradability: Not determined.

Bioaccumulative Potential: Not determined.

Mobility in Soil: Not determined

Section 13: Disposal Considerations

Spills and leaks: To prevent falls sweep up spills and place in waste container. Incinerate or dispose of in accordance with all applicable local, state and federal regulations.

Disposal Method: Any disposal practice must be in accordance with local, state, and federal regulations. For unused or uncontaminated material, the preferred disposal options are to send to a licensed recycler, reclaimer, or incinerator. The same disposal options are recommended for used, or contaminated material, but additional evaluation is required.

Section 14: Transport Information

US Department of Transportation (D.O.T) and Canadian TDG, does not regulate this product when shipped domestically by land.

Section 15: Regulatory Information

The information in this document is provided with good intentions and believed to be accurate, but no warranty is expressed or implied. Recipients are advised to confirm in advance of the need that the information is current, applicable, and suitable to their circumstances. Recipients are responsible for ensuring that its activities are in accordance with local, state and federal regulations. When shipped domestically by land, Canadian or US Department of Transportation does not regulate this product.

- The Canadian Workplace Hazardous Materials Information System (WHMIS) Classification for this product is "This product is not a "controlled Product" under WHMIS.
- SARA HAZARD CATEGORY: Not to have met any hazard category
- TOXIC SUBSTANCES CONTROL ACT (TSCA) and Canadian Domestic Substance List (DSL): All ingredients are on the TSCA/DSL inventory or not required to be listed on the TSCA/DSL inventory.
- THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA): This product is not a "hazardous Chemical" as defined by the OSHA hazard communication standard,

Section 16: Other Information

Abbreviations:

OSHA: The Occupational Safety and Health Administration.

CAS #: Chemical Abstracts Service number.

CA-65: California Proposition 65 (Safe Drinking Water & Toxic Enforcement Act)

RCRA: Resource Conservation and Recovery Act.